




Demand more. Choose Foster

## Eco Pro G2 1/3 Freezer Counter EP13L



### Temperature

---

 Freezer -18/-21 °C

### Dimensions (mm)

---

W 1865    D 700  
H 865

### Capacity

---

435 Litres

### Weight

---

Unpacked: 145 KG Packed: not available

### Features & Benefits

---

Providing excellence and practicality at a very competitive price, the Eco Pro range generates significant energy and carbon reductions in use saving you money on your operating costs whilst at the same time never compromising on your commitment to food safety

- High Quality 304 Stainless Steel Exterior Build Quality
- 60mm all-round insulation improves energy efficiency
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- Concealed refrigeration system maximises capacity with a tidy and practical interior

External Finish	
304 Stainless Steel	Standard
304 Stainless Steel Rear For Island Siting	Option

Internal Finish	
304 Stainless Steel	Option
Aluminium	Standard

Shelving	
Additional Shelf	Option
Nylon Coated Gastronorm 1/1 Shelf	Quantity: 6 Standard

Base Fittings	
80mm Castors	Standard
150mm Legs	Option
Levelling Bolts	Option

Doors	
Solid Full	Standard

Worktop & Drawers	
Worktop	Standard
100mm Splashback	Option
Less Worktop	Option

Refrigeration	
Forced Air	Standard
Integral	Standard
Remote - less condensing unit	Option
R290 (Hydrocarbon)	Standard
R404a	Option
Drain Required?	No


Electrical, Energy and Service Information	
230 Volts	Standard
50Hz	Standard
1 Phase	Standard
Running Watts	546
Running Amps	3.7
Thermal Heat Rejection (W)	556
Noise (dBa @ 1m)	68.3
Fuse Required (A)	10 amp
Refrigerant charge	0.14
Global Warming Potential	3
Energy Efficiency Index	64.78

Product Extras	
Helicoil Mains Lead	Option
Marine Kit	Option
Width Reduction (178mm reduction available when remote option selected)	Option

## Footnotes

- Marine kit option includes legs, bulkhead brackets, rat proofing & marine shelves.
- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm.
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm

# Energy Performance Data and information



## Application

This appliance is intended for use in ambient temperatures up to 40<sup>2)</sup>C

## Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

## Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [www.fosterrefrigerator.co.uk/Foster-OurPolicies.asp](http://www.fosterrefrigerator.co.uk/Foster-OurPolicies.asp)