



Product Code: LR360 13-118

Freezer Undercounter Cabinet



Features & Benefits

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Roller castors to rear for ease of movement
- Integrated door lock for security
- High quality magnetic door gasket
- Operate in ambient up to 40°C

External Finish

s/s ext Standard

Internal Finish

aluminium Standard

Shelving

Nylon Coated Shelf Option

Base Fittings

Levelling Bolts Standard

Doors

Solid Standard

Refrigeration

R134a - Industry Standard Standard

Electrical, Service & Ecodesign Data

230/50/1 Standard

Fuse Required 13

Global Warming Potential 3922

Energy Efficiency Index 92.49

Refrigerant Charge 0.270

Specification

Dimensions (Width) 1217

Dimensions (Height) 824

Dimensions (Depth) 755

Weight (Unpacked, kg) 90.5

Weight (Packed, kg) 104.51

Gross Volume 360

Noise DbA @ 1M TBC

Integral Refrigeration System Standard

Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for airflow, ensure that 25mm clearance is allowed above the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet



Application

This appliance is intended for use in ambient temperatures up to 40°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care