



## C402 – Undercounter Glasswasher

- 2 Year warranty
- **NEW** dual flow wash pump
- **NEW** parallel quick release wash & rinse arm design
- **NEW** surface scrap tray filters supplied as standard
- **NEW** alarms menu
- **NEW** molded wash tank for easy cleaning
- **NEW** molded rack guide giving partial double skin
- Supplied with two open cup/glass racks
- Optional drain pump
- Accurate detergent and rinse aid peristaltic dosing as standard
- Three standard cycle time options with further options available
- Cycle times can be tailored to site requirements
- Selectable energy saving mode
- Automatic self-cleaning at end of service
- Selectable thermostop ensures optimum rinse temperatures
- Operational self-diagnostics
- Bright LED display with soft touch controls
- Twin traffic light display indicates machine status



# C402 – Undercounter Glasswasher

	C402
Width	440mm
Depth	540mm
Height	665mm+Feet
Feet height	5mm-15mm
Basket size	390 x 390mm
Maximum useable height	300mm
Door Opening	320mm
Number of standard cycles	3
Standard cycle times	90/120/150 Seconds - adjustable
Special cycles	Plate cycle
Self-cleaning program	Partial clean
Water consumption per cycle	1.9 Litres
Wash tank capacity	10 Litres
Power – Single phase	240V, 2.8kW(13Amp)
Boiler element	2.6kW
Washtank element	1.4kW
Detergent pump	Peristaltic – Precise delivery
Rinse aid pump	Peristaltic – Precise delivery
Drain type	Manual drain plug
Drain pump	Optional
Breaktank	No - Glasswasher
Water supply pressure	2 to 4 Bar
Water supply temperature	10 to 50 Degrees Celsius
Body construction	Partial double skin
Door construction	Double Skin
Tank construction	Moulded
Scrap trays	Yes
Wash pump type	Dual flow
Wash pump power	180W
Wash arm - upper	Clip on composite parallel arms
Wash arm - lower	Clip on composite parallel arms
Rinse arm - upper	Combined with wash arm
Rinse arm - lower	Combined with wash arm
Open cup/glass basket	2
User interface (Controls)	Soft touch controls