



Evolution | undercounter



401 & 405 WS



501 & 505 WS

- 2 year warranty
- Full LCD display and user interface giving uncomplicated machine status updates
- Designed for the most demanding environments
- Breaktank as standard
- Double skinned minimising both acoustic output and reduced heat loss
- 405 WS & 505 WS with internal continuous water softener
- Low water consumption
- Three standard cycle options
- Extensive range of special cycle options
- PLATES cycle automatically changes parameters to suit plate washing
- NEW cycle on 401 & 405 WS gives a complete refresh of the wash water
- LONG cycle for intensive wash or for glass renovation on 501 & 505 WS
- STEEL cycle for the best results when washing cutlery on 501 & 505 WS
- Detergent and rinse aid delivery by precise peristaltic pumps
- Priming and dosing of chemicals enabled from fascia controls
- Comprehensive automatic self-cleaning cycle
- Drain pump as standard
- Surface scrap trays as standard
- Hi-level information retrieval to aid both installation and service technicians
- Supplied with two open cup/glass racks



Technical

- Standard voltage 240V – single phase
- 501 & 505 WS models can be supplied for 3 phase
- Suitable for hot (max 50°C) or cold* water supply at 2 to 4 bar dynamic supply pressure
- Wash temperature 60°C (adjustable)
- Rinse temperature 65°C (adjustable), 78°C when PRO Plates cycle selected
- Cycle times between 90 & 715 secs, including special cycles

Drain pump versions require a waste up-stand for correct operation.

Restrictive waste connections should be avoided for all installations.

*Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.

| Model | Rack size mm | Useable Height mm | Dimensions mm W x D x H | Standard Cycle Options | Power kW | Amps Required | Price |
|------------------|--------------|-------------------|------------------------------|------------------------|-------------|------------------------|--------|
| Evolution 401 | 400 | 270 | 470 x 560 x 700 [#] | 3 Cycles | 2.9 | 13 | £3,350 |
| Evolution 405 WS | 400 | 270 | 470 x 560 x 700 [#] | 3 Cycles | 2.9 | 13 | £3,740 |
| Evolution 501 | 500 | 250 | 600 x 605 x 715 [#] | 3 Cycles | 2.6/4.5/6.5 | 13/20/30 ^{##} | £3,750 |
| Evolution 505 WS | 500 | 250 | 600 x 605 x 715 [#] | 3 Cycles | 2.6/4.5/6.5 | 13/20/30 ^{##} | £4,180 |

[#] Height excludes adjustable feet which will add 10 to 20mm.

^{##} Machines will be supplied for 30 amp supply as standard, if 13 or 20 amp ordered they will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.

It is strongly recommended that 500mm machines are installed on hot water fill (max 50°C) for optimum performance.

See page 24 for ancillary items.