



# Halcyon Amika

## undercounter glasswashers



AMH35



AMH40



AMH45



51 XL & 55 XL WSD

(see next page for 50 XL image)

- 1 year warranty
- **NEW** dosing setup by fascia controls AMH35, AMH40, AMH45
- **NEW** easy clean parallel wash and rise arm assembly on AMH35, AMH40, AMH45
- **NEW** surface scrap trays standard on AMH45 and optional on AMH35, AMH40, 50 XL, 51 XL & 55 XL WSD
- Halcyon Amika models ruggedly built with simple controls
- 55 XL WSD with internal automatic water softener
- Large three button controls on AMH35, AMH40, AMH45 & 50 XL
- Simple soft touch wipe clean controls on 51 XL & 55 XL WSD
- All models fitted as standard with precise control peristaltic detergent and rinse aid dosing
- Drain pump as standard on 55 XL WSD, optional on all other models
- 51 XL & 55 XL WSD with internal breaktank as standard
- Reduced power consumption on the AMH35, AMH40, AMH45

### Technical

- Standard voltage 240V – single phase
- 50 XL, 51 XL & 55 XL WSD can be supplied for 3 phase operation
- Suitable for hot (max 50°C) or cold\* water supply at 2 to 4 bar dynamic pressure
- Wash temperature 60°C
- Rinse temperature for AMH35, AMH40, AMH45 & 50 XL 65°C
- Rinse temperature for 51 XL & 55 XL WSD 80°C

Drain pump versions require a waste up-stand for correct operation. Restrictive waste connections should be avoided for all installations.

\*Machines fitted to cold water supplies will not be capable of running repeated short cycles, the cycle time will automatically be extended to allow recovery of correct operating temperatures.

Model	Rack size mm	Useable Height mm	Dimensions mm W x D x H	Cycle Time Sec	Power kW	Amps Required
AMH35	350	240	400 x 495 x 590 <sup>#</sup>	120	2.75	13
AMH35 D	As AMH35 above with fitted drain pump					
AMH40	390	300	440 x 540 x 665 <sup>#</sup>	120	2.8	13
AMH40 D	As AMH40 above with fitted drain pump					
AMH45	450	280	525 x 560 x 705 <sup>#</sup>	120	2.8	13
AMH45 D	As AMH45 above with fitted drain pump					
AM 50 XL	500	325	580 x 605 x 815 <sup>#</sup>	90/150	2.6/4.5/6.5	13/20/30 <sup>##</sup>
AM 50 XLD	As AM 50 XL above with fitted drain pump					
AM 51 XL	500	325	580 x 605 x 815 <sup>#</sup>	90/150	2.6/4.5/6.5	13/20/30 <sup>##</sup>
AM 51 XLD	As Am 51 XL above with fitted drain pump					
AM 55 XL WSD	500	325	580 x 605 x 815 <sup>#</sup>	90/150	2.6/4.5/6.5	13/20/30 <sup>##</sup>
AM 55 XL WSD supplied with drain pump as standard						

# Height excludes feet which add 10 to 20mm.

## Machines will be supplied for 30 amp supply as standard, if 13 or 20 amp ordered they will be supplied with original cable and without plug. Standard 13 amp UK 3 pin plugs will be **unsuitable** for cable supplied.

**It is strongly recommended that for busy sites to achieve optimum performance that machines are installed on hot fill (max 50°C).**